

AXS2



Uninterruptible Power Supplies with battery - Intrusion / Access Control

12 V DC • 24 V DC



Complies with Standard: EN 50131 – 6 grade 2
“Alarm Systems, Intrusion and hold-up systems”

Communication by LED on the front panel • Dry Contact

The AXS2 Uninterruptible Power Supplies with battery provide permanent and backup power for Intrusion and Access Control installations.



DIN

105 x 90 x 62 mm



CG2

125 x 177 x 68 mm



C7

243 x 195 x 96 mm



C24

322 x 248 x 126 mm



C35

367 x 352 x 108 mm



C38

289 x 350 x 189 mm

Main functions

- ~ Resists short-circuits on load outlets
- ~ Controls and reports operating status
- ~ Resumes as soon as the mains returns
- ~ Opening and tamper contacts (on models with casing).

Benefits of the AXS2 range

- ~ One independent fuse-protected load outlet
- ~ Optional: card with 3 feeders and 5 feeders
- ~ Dimensioned to operate 24/7 at rated power
- ~ Built-in lightning protection.

AB = With Battery
SB = Without Battery

| MODEL | WEIGHT (kg) | SIZE W x H x D (mm) | CODE |
|---------------------------|-------------|---------------------|------------|
| AXS2 12V | | | |
| AXS2 12V 2A DIN | 0.2 kg | 105 x 90 x 62 | 2720220000 |
| AXS2 12V 2A C7 SB | 1.0 kg | 243 x 195 x 96 | 2720207000 |
| AXS2 12V 2A C7 AB 7AH | 4.0 kg | 243 x 195 x 96 | 2720207007 |
| AXS2 12V 2A C24 SB | 2.0 kg | 322 x 248 x 126 | 2720224000 |
| AXS2 12V 2A C24 AB 12 AH | 6.0 kg | 322 x 248 x 126 | 2720224012 |
| AXS2 12V 5A DIN | 0.2 kg | 105 x 90 x 62 | 2720520000 |
| AXS2 12V 5A C7 SB | 1.0 kg | 243 x 195 x 96 | 2720507000 |
| AXS2 12V 5A C7 AB 7AH | 4.0 kg | 243 x 195 x 96 | 2720507007 |
| AXS2 12V 5A C24 SB | 2.0 kg | 322 x 248 x 126 | 2720524000 |
| AXS2 12V 5A C24 AB 12 AH | 6.0 kg | 322 x 248 x 126 | 2720524012 |
| AXS2 12V 5A C24 AB 24 AH | 12.0 kg | 322 x 248 x 126 | 2720524024 |
| AXS2 12V 5A C35 SB | 2.7 kg | 375 x 360 x 138 | 2720535000 |
| AXS2 12V 5A C35 AB 7AH | 7.5 kg | 375 x 360 x 138 | 2720535007 |
| AXS2 12V 5A C35 AB 17AH | 9.2 kg | 375 x 360 x 138 | 2720535017 |
| AXS2 12V 5A C38 SB | 5.0 kg | 289 x 350 x 189 | 2720538000 |
| AXS2 12V 5A C38 AB 40AH | 20.0 kg | 289 x 350 x 189 | 2720538040 |
| AXS2 12V 10A CG2 | 1.0 kg | 125 x 177 x 68 | 2721002000 |
| AXS2 12V 10A C35 SB | 3.1 kg | 375 x 360 x 138 | 2721035000 |
| AXS2 12V 10A C35 AB 17AH | 8.5 kg | 375 x 360 x 138 | 2721035017 |
| AXS2 12V 10A C38 SB | 5.0 kg | 289 x 350 x 189 | 2721038000 |
| AXS2 12V 10A C38 AB 24 AH | 15.0 kg | 289 x 350 x 189 | 2721038024 |
| AXS2 12V 10A C38 AB 40 AH | 20.0 kg | 289 x 350 x 189 | 2721038040 |
| AXS2 24V | | | |
| AXS2 24V 1A DIN | 0.2 kg | 105 x 90 x 62 | 2740120000 |
| AXS2 24V 1A C7 SB | 1.0 kg | 243 x 195 x 96 | 2740107000 |
| AXS2 24V 1A C7 AB 1,2AH | 4.0 kg | 243 x 195 x 96 | 2740107001 |
| AXS2 24V 1A C24 SB | 2.0 kg | 322 x 248 x 126 | 2740124000 |
| AXS2 24V 1A C24 AB 7 AH | 8.0 kg | 322 x 248 x 126 | 2740124007 |
| AXS2 24V 2,5A DIN | 0.2 kg | 105 x 90 x 62 | 2740220000 |
| AXS2 24V 2,5A C24 SB | 2.0 kg | 322 x 248 x 126 | 2740224000 |
| AXS2 24V 2,5A C24 AB 7AH | 8.0 kg | 322 x 248 x 126 | 2740224007 |
| AXS2 24V 2,5A C24 AB 12AH | 10.0 kg | 322 x 248 x 126 | 2740224012 |
| AXS2 24V 2,5A C35 SB | 2.7 kg | 375 x 360 x 138 | 2740235000 |
| AXS2 24V 2,5A C35 AB 7AH | 7.9 kg | 375 x 360 x 138 | 2740235007 |
| AXS2 24V 2,5A C35 AB 17AH | 14.0 kg | 375 x 360 x 138 | 2740235017 |
| AXS2 24V 2,5A C38 SB | 5.0 kg | 289 x 350 x 189 | 2740238000 |
| AXS2 24V 2,5A C38 AB 24AH | 25.0 kg | 289 x 350 x 189 | 2740238024 |
| AXS2 24V 5A CG2 | 1.0 kg | 125 x 177 x 68 | 2740502000 |
| AXS2 24V 5A C35 SB | 3.1 kg | 375 x 360 x 138 | 2740535000 |
| AXS2 24V 5A C35 AB 17 AH | 8.5 kg | 375 x 360 x 138 | 2740535017 |
| AXS2 24V 5A C38 SB | 5.0 kg | 289 x 350 x 189 | 2740538000 |
| AXS2 24V 5A C38 AB 24AH | 17.0 kg | 289 x 350 x 189 | 2740538024 |