

Charger for PA / VA for 19" rack - Evacuation

24 V DC



Certified as per standard EN 54-4/A2

"Detection and fire alarm systems"

Certificates can be downloaded from www.slat.com

Communication by LED on the front panel • Dry contact

SONaes battery chargers associated with a battery can be used to back up public address safety systems for evacuation of buildings.



Rack 2U - front view
483 x 89 x 399 mm



Rack 2U - back view
483 x 89 x 399 mm

Main functions

- ~ Alarm currents can be configured from 40 A to 150 A.
- ~ Checks the presence and the impedance of the battery.
- ~ Protects the battery from temperature variations and deep discharge.
- ~ Alarm reports via dry contacts and locally.

Benefits of the SONaes range

- ~ Up to 6 amplifier outputs 40 A and 3 independent fused auxiliary outputs.
- ~ All connectors are pluggable.
- ~ Fully protected product, with rear connectors.
- ~ Integrated lightning protection.

| MODEL | WEIGHT (kg) | SIZE W x H x D (mm) | CODE |
|-----------------------------------|-------------|---------------------|------------|
| SONAES 24V | | | |
| SON 24V 6A MS 40 RACK | 3.1 kg | 483 x 89 x 355 | 4540633000 |
| SON 24V 12A MS 150 RACK | 5.4 kg | 483 x 89 x 399 | 4541233000 |
| FRONT TERMINAL BATTERY 24V | | | |
| BAT FRONT 24V 100Ah +CABLOT | 75.0 Kg | 1 tray | 6540000100 |
| BAT FRONT 24V 150Ah +CABLOT | 110.0 Kg | 1 tray | 6540000150 |