

AXS2



Uninterruptible Power Supplies with battery - Intrusion / Access Control

12 V DC • 24 V DC



Complies with Standard: EN 50131 – 6 grade 2
“Alarm Systems, Intrusion and hold-up systems”

Communication by LED on the front panel • Dry Contact

The AXS2 Uninterruptible Power Supplies with battery provide permanent and backup power for Intrusion and Access Control installations.



DIN
105 x 90 x 62 mm



C7
243 x 195 x 96 mm



C38
289 x 350 x 189 mm



CG2
125 x 177 x 68 mm



C24
322 x 248 x 126 mm



C34
367 x 352 x 108 mm

Main functions

- ~ Resists short-circuits on load outlets
- ~ Controls and reports operating status
- ~ Resumes as soon as the mains returns
- ~ Opening and tamper contacts (on models with casing).

Benefits of the AXS2 range

- ~ One independent fuse-protected load outlet
- ~ Optional: card with 3 feeders and 5 feeders
- ~ Dimensioned to operate 24/7 at rated power
- ~ Built-in lightning protection.

AB = With Battery
 SB = Without Battery

MODEL	WEIGHT (kg)	SIZE W x H x D (mm)	CODE
AXS2 12V			
AXS2 12V 2A DIN	0,2 kg	105 x 90 x 62	2720220000
AXS2 12V 2A C7 SB	1,0 kg	243 x 195 x 96	2720207000
AXS2 12V 2A C7 AB 7AH	4,0 kg	243 x 195 x 96	2720207007
AXS2 12V 2A C24 SB	2,0 kg	322 x 248 x 126	2720224000
AXS2 12V 2A C24 AB 12 AH	6,0 kg	322 x 248 x 126	2720224012
AXS2 12V 5A DIN	0,2 kg	105 x 90 x 62	2720520000
AXS2 12V 5A C7 SB	1,0 kg	243 x 195 x 96	2720507000
AXS2 12V 5A C7 AB 7AH	4,0 kg	243 x 195 x 96	2720507007
AXS2 12V 5A C24 SB	2,0 kg	322 x 248 x 126	2720524000
AXS2 12V 5A C24 AB 12 AH	6,0 kg	322 x 248 x 126	2720524012
AXS2 12V 5A C24 AB 24 AH	12,0 kg	322 x 248 x 126	2720524024
AXS2 12V 5A C34 SB	3,0 kg	367 x 352 x 108	2720517000
AXS2 12V 5A C34 AB 7AH	4,0 kg	367 x 352 x 108	2720517007
AXS2 12V 5A C34 AB 17AH	10,0 kg	367 x 352 x 108	2720517017
AXS2 12V 5A C38 SB	5,0 kg	289 x 350 x 189	2720538000
AXS2 12V 5A C38 AB 40AH	20,0 kg	289 x 350 x 189	2720538040
AXS2 12V 10A CG2	1,0 kg	125 x 177 x 68	2721002000
AXS2 12V 10A C34 SB	3,0 kg	367 x 352 x 108	2721017000
AXS2 12V 10A C34 AB 17AH	10,0 kg	367 x 352 x 108	2721017017
AXS2 12V 10A C38 SB	5,0 kg	289 x 350 x 189	2721038000
AXS2 12V 10A C38 AB 24 AH	15,0 kg	289 x 350 x 189	2721038024
AXS2 12V 10A C38 AB 40 AH	20,0 kg	289 x 350 x 189	2721038040
AXS2 24V			
AXS2 24V 1A DIN	0,2 kg	105 x 90 x 62	2740120000
AXS2 24V 1A C7 SB	1,0 kg	243 x 195 x 96	2740107000
AXS2 24V 1A C7 AB 1,2AH	4,0 kg	243 x 195 x 96	2740107001
AXS2 24V 1A C24 SB	2,0 kg	322 x 248 x 126	2740124000
AXS2 24V 1A C24 AB 7 AH	8,0 kg	322 x 248 x 126	2740124007
AXS2 24V 2,5A DIN	0,2 kg	105 x 90 x 62	2740220000
AXS2 24V 2,5A C24 SB	2,0 kg	322 x 248 x 126	2740224000
AXS2 24V 2,5A C24 AB 7AH	8,0 kg	322 x 248 x 126	2740224007
AXS2 24V 2,5A C24 AB 12AH	10,0 kg	322 x 248 x 126	2740224012
AXS2 24V 2,5A C34 SB	3,0 kg	367 x 352 x 108	2740217000
AXS2 24V 2,5A C34 AB 7AH	9,0 kg	367 x 352 x 108	2740217007
AXS2 24V 2,5A C34 AB 17AH	17,0 kg	367 x 352 x 108	2740217017
AXS2 24V 2,5A C38 SB	5,0 kg	289 x 350 x 189	2740238000
AXS2 24V 2,5A C38 AB 24AH	25,0 kg	289 x 350 x 189	2740238024
AXS2 24V 5A CG2	1,0 kg	125 x 177 x 68	2740502000
AXS2 24V 5A C38 SB	5,0 kg	289 x 350 x 189	2740538000
AXS2 24V 5A C38 AB 24AH	17,0 kg	289 x 350 x 189	2740538024