

# EVOLUTION RMS IP



Emergency power supplies with batteries in a 19" 2U rack IP Management

12 V DC • 24 V DC • 48 V DC

## Remote communication over IP and Digital Display

The emergency power supplies of the EVOLUTION RMS IP range provide permanent and backup power for all installations.



Rack 2U - front view  
483 x 89 x 395 mm



Rack 2U - back view  
483 x 89 x 395 mm

### Main functions

- ~ Controls and reports operating status over IP
- ~ Monitors battery presence
- ~ Protects the battery against deep discharge
- ~ Display of status on the front panel

### Benefits of the RMS IP range

- ~ Five fuse-protected load outlets
- ~ All connectors are pluggable
- ~ Built-in lightning protection
- ~ Fully-protected product, with rear connectors

MODEL	WEIGHT (kg)	SIZE W x H x D	CODE
<b>EVOLUTION RMS IP 12V</b>			
RMS IP 12V 8A 16A UTIL	3,7 kg	483 x 89 x 395	1521634000
RMS IP 12V 16A 32A UTIL	4,7 kg	483 x 89 x 395	1523234000
<b>EVOLUTION RMS IP 24V</b>			
RMS IP 24V 4A 10A UTIL	3,7 kg	483 x 89 x 395	1541034000
RMS IP 24V 10A 16A UTIL	4,7 kg	483 x 89 x 395	1541634000
<b>EVOLUTION RMS IP 48V</b>			
RMS IP 48V 2A 4A UTIL	3,7 kg	483 x 89 x 395	1580434000
RMS IP 48V 4A 10A UTIL	4,7 kg	483 x 89 x 395	1581034000