

Integrable emergency power supplies

12 V DC • 24 V DC • 48 V DC



Communication via dry contact

FIT'IN emergency power supplies provide permanent and backup power for all installations.



CG1
130 x 104 x 41 mm



CG2
125 x 177 x 68 mm



CG3
182 x 231 x 73 mm



CG4
215 x 265 x 77 mm

Main functions

- ~ Card protection, DIN rail mounting.
- ~ Battery charger function.
- ~ Resists short-circuits on load outlets.
- ~ The installation resumes as soon as the mains returns.

Benefits of the FIT'IN range

- ~ Two independent fuse-protected load outlets.
- ~ Dimensioned to operate 24/7 at rated power.
- ~ Built-in lightning protection.
- ~ Fits easily into an enclosure or cabinet.
- ~ Inaudible.

MODEL	WEIGHT (kg)	SIZE W x H x D (mm)	CODE	PACK
FIT'IN 12V				
FITIN 12V 6A CG1	0,5 kg	130 x 104 x 41	1520601000	-
FITIN 12V 6A CG1 Q16	0,5 kg	130 x 104 x 41	1520613000	16
FITIN 12V 12A CG2	1,0 kg	125 x 177 x 68	1521202000	-
FITIN 12V 12A CG2 Q16	1,0 kg	125 x 177 x 68	1521214000	16
FITIN 12V 24A CG3	2,2 kg	182 x 231 x 73	1522403000	-
FITIN 12V 24A CG3 Q8	2,2 kg	182 x 231 x 73	1522415000	8
FITIN 12V 32A CG4	3,5 kg	215 x 265 x 77	1523204000	-
FIT'IN 24V				
FITIN 24V 3A CG1	0,5 kg	130 x 104 x 41	1540301000	-
FITIN 24V 3A CG1 Q16	0,5 kg	130 x 104 x 41	1540313000	16
FITIN 24V 6A CG2	1,0 kg	125 x 177 x 68	1540602000	-
FITIN 24V 6A CG2 Q16	1,0 kg	125 x 177 x 68	1540614000	16
FITIN 24V 12A CG3	2,2 kg	182 x 231 x 73	1541203000	-
FITIN 24V 12A CG3 Q8	2,2 kg	182 x 231 x 73	1541215000	8
FITIN 24V 24A CG4	3,5 kg	215 x 265 x 77	1542404000	-
FITIN 24V 24A CG4 Q4	3,5 kg	215 x 265 x 77	1542416000	4
FIT'IN 48V				
FITIN 48V 3A CG2	1,0 kg	125 x 177 x 68	1580302000	-
FITIN 48V 3A CG2 Q16	1,0 kg	125 x 177 x 68	1580314000	16
FITIN 48V 6A CG3	2,2 kg	182 x 231 x 73	1580603000	-
FITIN 48V 6A CG3 Q8	2,2 kg	182 x 231 x 73	1580615000	8
FITIN 48V 12A CG4	3,5 kg	215 x 265 x 77	1581204000	-
FITIN 48V 12A CG4 Q4	3,5 kg	215 x 265 x 77	1581216000	4