

Charger for PA / VA for 19" rack - Evacuation

24 V DC • 48 V DC



Certified as per standard EN 54-4/A2

“Detection and fire alarm systems”

Certificates can be downloaded from www.slat.com

Communication by LED on the front panel • Dry contact

SONaes battery chargers associated with a battery can be used to back up public address safety systems for evacuation of buildings.



Rack 2U - front view
483 x 89 x 399 mm



Rack 2U - back view
483 x 89 x 399 mm

Main functions

- ~ Alarm currents can be configured from 40 A to 150 A.
- ~ Checks the presence and the impedance of the battery.
- ~ Protects the battery from temperature variations and deep discharge.
- ~ Alarm reports via dry contacts and locally.

Benefits of the SONaes range

- ~ Up to 6 amplifier outputs 40 A and 3 independent fused auxiliary outputs.
- ~ All connectors are pluggable.
- ~ Fully protected product, with rear connectors.
- ~ Integrated lightning protection.

MODEL	WEIGHT (kg)	SIZE W x H x D (mm)	CODE
SONAES 24V			
SON 24V 6A MS 40 RACK	3,1 kg	483 x 89 x 355	4540633000
SON 24V 12A MS 150 RACK	5,4 kg	483 x 89 x 399	4541233000
FRONT TERMINAL BATTERY 24V			
BAT FRONT 24V 100Ah +CABLOT	75 Kg	1 tray	6540000100
BAT FRONT 24V 150Ah +CABLOT	110 Kg	1 tray	6540000150
SONAES 48V			
SON 48V 12A MS 150 RACK	6,0 kg	483 x 89 x 399	4581233000
FRONT TERMINAL BATTERY 48 V			
BAT FRONT 48V 100Ah +CABLOT	142,4 kg	1 tray	6580000100
BAT FRONT 48V 150Ah +CABLOT	208,0 kg	1 tray	6580000150